

Safety group BI15 EN1488 - 1/2" 15mm

WATTS®





Watts Industries France


**WWATTS WWATTS**® SAFETY GROUP BI15 **SAFETY GROUP BI15** 

# Purpose:

This safety group is specifically designed to protect hot water storage heater (electric, gas ...) with a power up to 10 kW.


This device allows 4 main functions:


- protect the hot water storage heater against excess pressure, this function is assumed by the safety valve set at
- isolate the tank from the main water supply, this function is assumed by the isolating valve
- prevent the backflow from the hot water to cold main water supply, this protection is assumed by the integrated check-valve (BELGAQUA approved)
- -flush the hot water storage heater : if needed the safety valve allows the total draining of the hot water storage heater



- can be installed in any position
- new air gap according EN1488 (22 mm)
- valve knob designed for excellent grip
- isolating valve with EPDM seal
- BELGAQUA approved
- manufactured by the rst European producer of safety group (more than 2 millions safety group installed)

#### Dimensions:







BELGAQUA


Part	es list	
Мас	chined forged body	Brass CW617N
Valv	ve diaphragm	EPDM 70 SH
Valv	ve seat	Brass CW617N
valv	ve knob	PP-TF20
Air ç	gap	PP
Valv	e axis	PPO+PS-GF30
Valv	ve seal	EPDM
Che	ck-valves	POM
Plas	tic plug	PA-GF30

## Pressure drop curve / headloss:



## Pressure drop curve / headloss:





BI15 can be installed either vertical or horizontal position

The photographs and descriptions in this brochure are purely informational and in no way binding, Watts Industries reserves the right to make any technical or exterior changes deemed necessary to their products without prior notifica-

**WWATTS WWATTS**® **SAFETY GROUP BI15 SAFETY GROUP BI15** 


### Purpose:

This safety group is specifically designed to protect hot water storage heater (electric, gas ...) with a power up to 10 kW.

This device allows 4 main functions:


- protect the hot water storage heater against excess pressure, this function is assumed by the safety valve set at
- isolate the tank from the main water supply, this function is assumed by the isolating valve
- prevent the backflow from the hot water to cold main water supply, this protection is assumed by the integrated check-valve (KIWA and BELGAQUA approved)
- -flush the hot water storage heater : if needed the safety valve allows the total draining of the hot water storage heater


# **DESIGN**



- extra compact dimensions
- can be installed in any position
- new air gap according EN1488 (22 mm)
- valve knob designed for excellent grip
- isolating valve with EPDM seal
- KIWA approved
- BELGAQUA approved
- manufactured by the first European producer of safety group (more than 2 millions safety group installed)


### Dimensions:






kiwa


BELGAQUA




# Pressure drop curve / headloss:



## Pressure drop curve / headloss:





BI15 can be installed either vertical or horizontal position

The photographs and descriptions in this brochure are purely informational and in no way binding, Watts Industries reserves the right to make any technical or exterior changes deemed necessary to their products without prior notification.



Safety group BI15 EN1488 - 1/2" 15mm

WATTS®





Watts Industries France